



MTM5000 SERIES BENEFITS

EXTENDED OPERATIONAL RANGE

- Up to 10W transmit power (MTM5400/5500) and with class leading receiver sensitivity delivers comprehensive network coverage
- Integrated DMO Gateway, DMO Repeater capabilities (MTM5400/5500), ensure secure and resilient communications where needed most

SUPERIOR AUDIO PERFORMANCE

- Enhanced audio architecture delivering the loudest and clearest audio performance of any Motorola TETRA mobile available on the market*

HIGH SPEED DATA CONNECTIVITY

- TEDS Ready hardware - with a simple software license upgrade, enables 20x faster data connectivity for accessing back-office systems and databases
- Integrated USB 2.0 PEI, enabling rapid radio programming and standardised interfacing to data terminals and accessories. For additional flexibility, USB host and slave modes are also supported

LOW USER MIGRATION COSTS

- Familiar cellular style user interface and high resolution colour display for enhanced usability and reduced staff training costs
- Same intuitive user interface as latest MTP3000 Series and MTP6000 Series TETRA portable radios
- Re-use of common accessories using GCAI connector

ENHANCED END TO END ENCRYPTION OPTIONS

- Integrated hardware for SIM based end to end encryption
- Universal Crypto Module option**

* Assuming the appropriate audio accessory is used ** Model specific

LOCATION SERVICES

- The MTM5000 Series supports Global Navigation Satellite Systems (GNSS) based location services for GPS, GLONASS and BeiDou, as well as Satellite Based Augmentation Systems (SBAS) including WASS, EGNOS, MSASA, GAGAN and QZSS (Japan)

ADVANCED TERMINAL MANAGEMENT

- USB 2.0 interface for fast radio programming via Motorola Solutions Integrated Terminal Management (ITM) solution

FLEXIBLE INSTALLATION OPTIONS

- Fully DIN-A compatible and available in Dash, Desk, Remote Head and Motorcycle mount formats
- Supports multiple control heads - an ideal solution for installations in trains, ambulances and fire vehicles where more than one control point might be required
- Supports multiple transceivers - an ideal solution for multiple agency, joint operations, or multi-task communications including bilateral such as cross-border operations
- MTM5500 ethernet style connections enable up to 40m separation to either the new ReCH Control Head or the TSCH (IP55)
- Other Equipment Manufacturer (OEM) control head solutions can be developed using the Remote Display Control (RDC) protocols

RUGGED DESIGN WITH EXCEPTIONAL RELIABILITY

- Includes IP67 control head option, for exposed and challenging environments
- Front and Rear rugged GCAI connector for reliable connection of audio and data peripheral equipment
- Mobile radio and accessories are performance matched for enhanced reliability



MTM5000 SERIES SPECIFICATIONS



MODELS - COMPLIANT WITH DIN 75490 (ISO 7736)

	MTM5400	MTM5500
Dash	Compact radio for fast vehicle installation	N.A.
Desk	Compact radio, for use in the office. Optional range of accessories such as desk tray with integrated loudspeaker	N.A.
Multiple Remote Control Head	N.A.	Radio with multiple remote mount control head capability
	N.A.	Range of installation options enable use in cars, vans and other vehicles
Multiple Transceiver or Control	N.A.	Range of installation options enable use in cars, vans and other vehicles
Motorcycle	Environmentally enhanced radio meeting IP67 specification. Suitable for demanding environments such as motorcycle, fire appliance and marine installations	N.A.
Expansion head "Databox"	Radio without a control head, for data applications, or customised application development	

GENERAL

	Dimensions HxWxD (mm)	Weight Typical (g)	Dimensions HxWxD (mm)	Weight Typical (g)
Dash and Desk models (transceiver + control head)	60x188x198	1300	N.A.	N.A.
Transceiver only	45x170x169	1070	45x170x169	1070
Standard control head	60x188x31	230	N.A.	N.A.
Remote control head	60x188x39	300	60x188x39	300
Motorcycle control head	60x188x39	320	N.A.	N.A.

USER INTERFACE & DISPLAY

Display	Diagonal dimension	2.8"
	Type	640x480 pixels Transflective TFT, 65,000 colours
	Backlight	Variable backlight, User configurable
	Font sizes	Standard & Zoom mode (90 pixels, 4.5mm high) characters
TSCH		N.A. Available as option*
Buttons & Keypad	Numeric	Integral backlit numeric keypad of 12 keys, with keypad lock option
	International keypad versions	Roman, Arabic, Cyrillic, Korean, Chinese, Taiwanese characters**
	Programmable function keys	3 programmable function keys (plus 10 programmable numeric keys)
	Navigation	4-way navigation key, menu and soft keys
	Emergency	Emergency button with backlight
Rotary	Shortcuts	User configurable shortcuts to menus and common features using "One-Touch-Button" feature
	Dual Function	Talkgroup and volume change with lock option
Indication	LED	Tri-colour LED
	Tones	Configurable notification tones
User Interface Languages	Standard Options	Arabic, Chinese Simplified, Chinese Traditional, Croatian, Danish, Dutch, English, French, German, Greek, Hebrew, Hungarian, Italian, Korean, Lithuanian, Macedonian, Mongolian, Norwegian, Portuguese, Russian, Spanish, Swedish
	User defined	User programmable, using ISO 8859-1 character
Menu		Tailored to user needs
		Menu Shortcuts
		Menu Configuration
Contacts Management		Cellular Type
Contact List		Up to 1000 contacts
Multiple Dialling Methods		Up to 6 numbers per contact, Max 2000 numbers
Fast/Flexible Call Response		User selects how to dial
Multiple Ring Tones		Private Call Response to a Group Call via One Touch Button
Message Manager		Configurable with CPS
Text message list		Cellular Type
Intelligent Keypad Text Input		20
Status list		All Control Heads
Country/Network Code List		400
Scan lists		100
Discrete Mode		40 lists of 20 groups
Screen Saver		All Control Heads
Universal Time Display		gif image & text (any user's selection)
Keypad Lock		All Control Heads
Talkgroup Folders		Dual layer folder structure (folder/subfolder)
		256 folders
Favourite Folders		Up to 3 (to store any favourite talkgroup)

* Please refer to the separate specification sheet

** For availability of other language keypads please contact your local MSI representative

MTM5000 SERIES SPECIFICATIONS

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature (°C)		-30 to +60
Storage Temperature (°C)		-40 to +85
Not in use - Storage	ETSI 300 019-1-1 CLASS 1.3	Non-Weather Protected Storage Locations
Not in use - Transportation	ETSI 300 019-1-2 CLASS 2.3	Public Transportation
Stationary use - Weather Protected Locations	ETSI 300 019-1-3 CLASS 3.2	Partly Temperature Controlled Locations
Mobile use - Ground Vehicle Installation	ETSI 300 019-1-5 CLASS 5.2	Climatic Tests
Mobile use - Ground Vehicle Installation	ETSI 300 019-1-5 CLASS 5M3	Mechanical Tests
Rail Certification Environmental	EN50155:2007 and IEC60571 ED.3.0	Environmental
MIL STD	810 C/D/E/F/G Specifications	All 11 categories met (or exceeded)
Dust and Water Ingress Protection	IP54 (dust cat. 2) IP67	Dash/Desk/Remote models Motorcycle model (only control head is IP67; transceiver is IP54)
		MTM5500 TSCH IP55

ELECTRICAL SPECIFICATIONS

		MTM5400	MTM5500
Voltage Range		10.8 to 15.6 V DC	
Current Consumption (A, typ.)	Idle / Rx / Tx @ 10W	10W	0.5 / 1.0 / 1.2 (TX 3.4A Peak)
	Idle / Rx / Tx @ 3W		0.5 / 1.0 / .9 (TX 2.2A Peak)
	Tx - Multi Slot PD (4 slots) @ 5.6W	5.6W	2.7
	Tx - TEDS @ 3W		2.3
Using USB host		Adds 0.5A	

RF SPECIFICATIONS

Frequency Bands (MHz)	350 - 390, 380 - 430, 410 - 470, 806 - 870
Transmitter RF Power	TX Power 10W and 3W (Class 2 and Class 3)
RF Power Control	6 Power Step Levels (steps of 5 dBm) Starting at 15 dBm; finishing at 40 dBm
Receiver Class	A & B
Receiver Static Sensitivity (dBm)	-114 minimum, -116 typical (ETSI 300-392-2)
Receiver Dynamic Sensitivity (dBm)	-105 minimum, -107 typical (ETSI 300-392-2)

GPS SPECIFICATIONS

Simultaneous Satellite Systems	GPS plus one other GNSS, eg GLONASS, BeiDou
Mode of Operation	Concurrent tracking, SBAS capable, 72 channel
GNSS Antenna	Supports active antenna (5V, 25mA supply)
Autonomous Acquisition Sensitivity	-163 dBm
Tracking Sensitivity	-163 dBm
Location Protocols	ETSI Location Information Protocol (LIP) Motorola LRRP

VOICE SERVICES

Talkgroups	10,000 TMO, 2000 DMO	
Phone book entries	1000 persons. Up to 6 numbers per entry (mobile, office etc). Max 2000 entries	
Scan lists	40 lists of 20 talkgroups	
Trunked Mode (TMO) Services	Group call	Late Entry, TMO/DMO Mapping
	Private call	Half / Full Duplex
	Telephony (PABX, PSTN, MS-ISDN)	Full Duplex
	DGNA	Up to 10,000 groups
Direct Mode (DMO) Services	Scanning	Attachment signalling, supports SWMI initiated attachment/detachment
		Group call Private call
Emergency (tailored by users)	Tactical	Emergency Group Call to ATTACHED talkgroup
	Non-Tactical	Emergency Group Call to DEDICATED talkgroup
	Individual	Emergency Call to PREDEFINED party (half/full duplex)
	Smart emergency	TMO/DMO/DMO to TMO automatic switching options
	Hot Mic	Configurable timers for automatic open mic (talk without PTT)
	Location	Location (GPS) sent with emergency
	Target Address	Sent to individual or group address (selected or dedicated)
Alarm (status message)	Emergency Status (or other pre-defined status)	

DATA SERVICES

Status	Alias messages	400 Entries
	Options	Can be sent via One-Touch or via menu
Short Data Service (SDS)	Inbox	200 Entries (short messages), 40 Entries (long messages of up to 1000 characters)
		Cellular style iTAP predictive text entry
	Target Address	Sent to individual or group address (selected or dedicated)
Packet Data (PD)	Voice Call Interaction	SDS messages can be sent and received during a voice call
	Multi-slot PD	Data transmission with up to 4 slots supporting up to 28.8 kbit/s gross
TEDS (capable)	TETRA Enhanced Data Service (TEDS) (via software upgrade)	Supporting 25kHz and 50kHz channel bandwidths and enabling practical data rates of up to 80kbit/s
		QAM Channels: 25 kHz and 50 kHz (but not D8PSK channels) QAM modulation/coding modes: 4-QAM R1/2, 16-QAM R1/2, 64-QAM R1/2, and 64-QAM R2/3
WAP	Integrated WAP browser (including WAP-PUSH)	Integrated Openwave browser
		WAP 1.2.x and WAP 2.0 compatibility for UDP/IP Stack
Peripheral Equipment Interface (PEI)	Interface Protocol	AT Commands - Full Set ETSI Mandatory Compliant
		AT Multiplexer - 4 Virtual Physical Port (simultaneous PD, SDS, AT commands and Air Tracer SESSIONS) TNP1; enables simultaneous PD and SDS sessions
Terminal Management		Programmable via Motorola Integrated Terminal Management (iTM) solution

GATEWAY SERVICES

	MTM5400	MTM5500
DMO/TMO Gateway		Group voice calls from DMO to TMO
		Group voice calls from TMO to DMO
		Emergency group call from DMO to TMO
		Emergency group call from TMO to DMO
		Call Pre-emption (in either direction)
		SDS messaging from DMO to TMO (including GPS) or from TMO to DMO*
		Configurable routing of SDS messages to console or PEI*
		Intelligent handling of point to point calls and SDS messages whilst operating as a Gateway*

REPEATER SERVICES

DMO Repeater		Repeats DMO voice calls on selected talkgroup
		Repeats SDS and Status messaging on selected talkgroup*
		ETSI type 1A DMO Repeater for channel efficient operation
		Transmission of Repeater Presence Signal
		Priority Call
		Emergency Call (Pre-emptive Priority Call)
		E2EE Encrypted DMO traffic
		Monitoring of and participation in calls whilst in Repeater mode Configurable Repeater Power Levels

INTERFACES

RS232		Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT
USB		USB 2.0 support for PEI (Two Virtual Ports via standard Windows drivers enable PC applications to run simultaneously Packet Data and AT Commands)
		USB 2.0 support for PEI (Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT); rapid programming
		USB On-The-Go (host & slave) capability for intelligent PEI applications
		USB 1.1 support (Host Mode) to manage USB Slave Devices (e.g. SIM CARD READER)
Rugged Accessory Connector (GCAI)		GCAI - Motorola accessory and ancillary interface for connection of accessories, data terminals and programming
General Purpose Input/Output	Digital I/O	7 (4 on remote and motorcycle control head, 3 on transceiver)
	Analog input	4 (1 on remote and motorcycle control head, with 4 levels)

SECURITY FEATURES

Air Interface Encryption	Algorithms	TEA1, TEA2, TEA3
	Security Classes	Class 1 (Clear), Class 2 (SCK), Class 3G
	Authentication	Infrastructure initiated and made mutual by terminal
Provisioning		Secure provisioning tool via Key Variable Loader (KVL) PIN/PUK code access
User Access Control	Service Profile Selection for Radio User Assignment / Radio User Identity (RUA/RUI) Operation	Based on login credentials, a radio user can be limited to only those radio capabilities defined in pre-installed service profiles, selected by the infrastructure
Data		Packet Data user authentication
End to End Encryption (E2EE)	Voice E2EE	Enhanced End to End Encryption with OTAR supported through Universal Crypto Module (UCM) and SIM (via integrated card slot) and/or Cryptr 2 Broadband IP unit.
	Packet Data E2EE	
	Short Data (SDS) E2EE	

REGULATORY COMPLIANCE

Radio (R&TTE Article 3.2)		EN 303 035-1
		EN 303 035-2
		ETSI EN 300-394-1
		ETSI EN 300-392-2
EMC (R&TTE Article 3.1.b)		EN 301 489-1 V1.3.1
		EN 301 489-18 V1.3.1
Electrical Safety (R&TTE Article 3.1.a)		EN 60950-1 (2001)
		EN50360:2001 EME
Environmental		Directive 2002/96/EC WEEE
		EN50155:2007 (IEC 60571 ED. 3.0)
Automotive		E-mark, Automotive EMC Directive 95/54/EC
Rail Certification EMC		EN50121-3-2:2006 (IEC 62236-3-2 Ed.2.0)

* Future software release

For more information, please visit: motorolasolutions.com/MTM5000

Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, UK.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2018 Motorola Solutions, Inc. All rights reserved. 0218